PRODUCT COMPARISON OF MOST POPULAR BRANDS

	FRU		(K	POPUL	(MINDS	K	- KI	
MANUFACTURERS BRAND >>>>	Amvic	Arxx	Build Block	<u> </u>		IntegraSpec		Nudura	Polysteel	Quad-Lock	Reward
FEATURES			(Upo	lated June 11,	, 2006. Next u	pdate when not	tified of manu	ıfacturers chan	ges)		
45° Corners	Х	X	X	X	Х	X	X	X		X	Х
90° Corners	Х	X	X	X	Х	X	X	X	X	X	Х
Adjustable Corners		X				X					
Brick Ledge Attachment (Molded)						X		X			
Brick Ledge – Single side	Х	X	X	X	X	X	X	X			
Brick Ledge – Double side				X		X		X			
Cavity Size – 4"	Х	Х		X	X	?	Х	X	Х	X	?
Cavity Size – 6"	X	X	X	X	X	X	Х	X	Х	X	Х
Cavity Size – 8"	Х	Х	X	X	X	X	Х	X	Х	X	Х
Cavity Size – 10"	X	X		X		X	X	X	X	X	Χ
Cavity Size – 12"				X	X	X		X	X	X	?
Country of Origin	Canada	Canada	USA	USA	USA	USA & CAN	Canada	Canada	Canada	Canada	USA
# Manufacturing Plants	Yes-6	Yes-9	USA-8	Yes	Yes	Yes	Yes	Can-1/USA-1	Yes		Yes
Custom Cut Radius Walls	X					X		X			
Dimensions – Length x Height	48" x 16"	48" x 16.75"	48" x 16"	48" x 16"	48" x 12"	48" x 12"	48" x 16"	96" x 18"	48" x 20"		48" x 16"
Fire Rating	3-hour	4-hour	3-hour	3-hour	3-hour	3-hour	4-hour	4-hour	3-hour	3-hour	3-hour
Folds Flat and/or Ships Flat				X	Both	Ships flat		Both			
Fastening Strip Width	1 1/2	1 1/8	1 1/2		1 1/2	1 5/8		1 1/2	1 1/2		
Fastening Strip on inch Centers	6"	8"	6"	?	6"	8"	8"	8"	6"		?
Height Adjuster Strips	X	Х			Х	X		X			
Locking Fastening Strip						X		X			
Molded T-Form						X		X			
Pull-out Strength (using Drywall screw)	198 lbs	510 lbs	490 lbs			153 lbs	169 lbs	399 lbs			
Shear Strength		521 lbs	342 lbs			200 lbs	367 lbs				
Pre-assembled at Factory	X	X	X			X	X	X	X		X
Reversible Interlock (no top or bottom)	X		X			X		X			X
Standard Foam Thickness (in inches)	Х	2 5/8	Х	X	2 5/8	2 1/2	Х	2 5/8			2 3/4
Tapered Top - Single side				Х		Х	Х	Х			
Tapered Top – Double side	Х	Х		X	Х	Х		Х			
Number of Building Code Approvals	4	7	3		3	10					
Factory Training Program	Х	Х		X	Х	Х	Х	Х	Х		Х
Member of ICFA		Х	Х	Х	Х	Х	Х		Х		Х
Other											